

**200KG** 占地面积小，应用场所广。

**SKF** 采用进口SKF轴承，提高使用寿命和精度。

CE标准，安全，静音。

车钻铣三合一体机，钻头可升降，可360°旋转。

车削工作的横向进给的燕尾导轨配可调节的锥度镶条，耐磨损、面接触，刚性好。

调节皮带位置，可获得不同转速；

推拉式离合装置，可自由切换车削/钻铣切换。

The whole machine is 200KG, occupies a small area and has a wide range of applications.

Imported SKF bearings are used to improve service life and accuracy.


CE standard, safe, silent.

Turning, drilling and milling three-in-one machine, the drilling and milling head can be raised and lowered, and can be rotated 360°.

The lateral feed dovetail guide for turning work is equipped with an adjustable taper insert, which is resistant to wear, surface contact and has good rigidity.

Adjust the belt position to obtain different speeds;

Push-pull clutch device can switch between turning/drilling and milling freely.



型号	Model	CT300
车削	Turning	
床身回转直径	Swing over bed	300mm
中拖板回转直径	Swing over cross slide	140mm
两顶尖距	Distance between Centres	500mm
主轴孔锥度	Spindle taper	MT4
主轴通孔直径	Spindle bore	26mm
尾座套筒行程	Tailstock ram travel	50mm
尾座套筒锥度	Tailstock taper	MT3
中拖板横向行程	Lateral stroke	200mm
小刀架拖板行程	Top slide travel	80mm
公制螺纹 (种数)	Metric threads (Grade)	0.5~3mm (14)
英制螺纹 (种数)	Inch threads (Grade)	11~40 T.P.I. (20)
纵向进刀量	Range of Longitudinal Feed	0.036、0.072mm
主轴转速 (级数)	Spindle speeds (Grade)	160~1600r/min (6)
钻铣	Drilling and milling	
最大钻孔直径	Max. drilling diameter	20mm
工作台尺寸	Table size	200x150mm
T型槽尺寸	T-slots size	12mm
钻头箱垂直升降行程	Head travel	80mm
主轴锥度	Spindle taper	MT3
主轴行程	Spindle travel	80mm
主轴轴心到立柱导轨距离	Max. Spindle to Column	175mm
主轴端至工作台面最大距离	Max. Spindle to Table	240 ~ 320mm
主轴转速/级数	Spindle speeds (Grade)	125 ~ 1600r/min (12)
钻头箱绕立柱回转角度	Head Rotation	360°
其他	Other	
电机功率	Motor power	750W
净重	N.W.	200KG
外形尺寸	Overall dimensions	1160x580x900mm

产品外形尺寸为手工测量，存在较小误差，为正常情况，具体以实物为准。  
The dimensions of the product are measured manually, and there is a small error, which is normal, and the actual product shall prevail.

