工作室、科教机构共同的选择 更好的机械科技启蒙教育

学校、科创中心及科研单位教学演示使用,适合家用DIY,航模零件、钟表零件加工。

- 1、整机60kg, 占地面积小, 应用场所广。
- 2、双V形高频淬火导轨, 耐磨、稳定, 精度高。
- 3、丝杆防护罩,有效防止废削破坏丝杠,影响进度和使用使用
- 4、CE标准的断电护罩, 打开保护罩自动断电, 安全可靠。
- 5、高强度金属齿轮, 多契带传动。
- 6、主轴转速无级调速,调整皮带位置,切换高低挡位,50~1250&100~2500r/min,方便加工不同工件需求。

Common choice for studios and scientific and educational institutions Better Enlightenment Education in Mechanical Technology

For teaching demonstrations in schools, science and innovation centers and scientific research units, Suitable for home DIY, model aircraft parts, clock parts processing.


- 1, the whole machine 60kg, covers an area of small, wide application.
- 2, double V-shaped high-frequency quenching guide rail, wear-resistant, stable, high precision.
- 3, lead screw protective cover, effectively prevent waste cutting damage to the lead screw, affecting the progress and use
- 4, CE standard power protection cover, open the protective cover automatic power off, safe and reliable.
- 5, high strength metal gear, multi belt drive.
- 6, the spindle speed is stepless speed regulation, adjust the belt position, switch the high and low gear, 50~1250&100~2500r/min, convenient processing of different workpiece needs.













型号	Model	WM210V	WM210VL
床身回转直径	Swing over bed	210mm	
中拖板回转直径	Swing over cross slide	140mm	
两顶针最大距离	Distance between centers	400mm	500mm
主轴孔锥度	Spindle taper	мтз	
主轴通孔直径	Spindle bore	22mm	
尾座套筒行程	Tailstock ram travel	60mm	
尾座套筒锥度	Tailstock taper	MT2	
中拖板行程	Cross slide travel	75mm	
刀架拖板行程	Top slide travel	55mm	
公制螺纹	Metric threads	0.3~3.0mm (14)	
英制螺纹	Inch threads	10~44T.P.I. (10)	
纵向进给量	Range of Longitudinal Feed	0.089、0.147、0.198 mm/r	
主轴转速 (无级调速)	Spindle speed range (Variable)	50~1250 100~2500RPM	
电机功率	Motor power	750W	
净重	N.W.	60Kg	71Kg
外形尺寸	Package Size	820x400x340mm	920x400x340mm

产品外形尺寸为手工测量,存在较小误差,为正常情况,具体以实物为准。 The dimensions of the product are measured manually, and there is a small error, which is normal, and the actual product shall prevail.

WWW.AHCTIX.COM