

工业级家用钻铣床

Industrial domestic drilling and milling machines

高精度稳定铣削
 高强度轻松钻孔
 自动反转攻丝

SKF 采用进口SKF轴承，提高使用寿命和精度。

主轴箱头可升降，可左右倾斜90°。
 三轴采用燕尾导轨，配可调节锥度镶条，耐磨损，可重载
 面接触、刚性好。

750W主轴直驱电机，无级调速100~2500rpm


High-precision and stable milling
 High strength and easy drilling
 Automatic reverse tapping
 Imported SKF bearings are used to improve service
 life and accuracy.
 The three-axis adopts dovetail guide rail with
 adjustable taper inserts, which is wear-resistant,
 heavy-duty, surface-contact, and rigid.
 750W spindle direct drive motor, stepless speed
 regulation 100~2500rpm



三轴数显
 Three-axis digital display

自动走刀器
 Automatic knife feeder

广泛用于工厂、维修店铺、学校、科创中心及科研单位教学演示使用，适合家用DIY，航模零件、钟表零件加工；
 可加工钛、不锈钢、45号钢、铁、铝、铜等各类有色金属和木材、尼龙等各类软材料。
 Widely used in factories, maintenance shops, schools, science and technology innovation centers and scientific research units teaching demonstration use,
 suitable for household DIY, model airplane parts, clock parts processing;
 Can process titanium, stainless steel, 45 steel, iron, aluminum, copper and other non-ferrous metals and wood, nylon and other soft materials.



型号	Model	X25
最大钻孔直径	Drilling Capacity	25mm
最大面铣能力	Face Milling Capacity	63mm
最大立铣能力	End Milling Capacity	16mm
工作台尺寸	Table size	700x180mm
T型槽尺寸	T-slots size	12mm
工作台行程 (X,Y行程)	Table travel (X-, Y-Axis)	485, 140mm
主轴锥度	Spindle taper	R8/M12
主轴行程	Spindle stroke	70mm
主轴轴心到立柱导轨距离	Max. Spindle to Column	160mm
主轴端面至工作台面距离	Max. Spindle to Table	370mm
主轴箱左右倾斜	Head tilt	±90°
主轴转速 (无级变速)	Spindle speeds (Variable)	100~2500rpm
电机功率	Motor Power	750W
净重	N.W.	123KG
外形尺寸	Overall dimensions	960x580x780mm

产品外形尺寸为手工测量，存在较小误差，为正常情况，具体以实物为准。
 The dimensions of the product are measured manually, and there is a small error, which is normal, and the actual product shall prevail.