工业级重型自动进给钻铣床

Industrial grade automatic feed drilling and milling machine

工业级攻、钻、铣三用

高精度稳定铣削

高强度轻松钻孔

限位自动反转攻丝

主轴自动进给

主轴箱自动升降、可左右倾斜45°

三轴采用燕尾导轨,配可调节锥度镶条,耐磨损,可重载 面接触、刚性好。

1.5KW大功率异步电机

提供强劲动力,性能佳、寿命长、效率高.

Industrial grade tapping, drilling and milling

High-precision and stable milling

High strength and easy drilling

Limit automatic reverse tapping

Spindle automatic feed

The headstock can be automatically raised and lowered,

and can be tilted 45° left and right

The three-axis adopts dovetail guide rail with adjustable taper inserts, which is wear-resistant, heavy-duty,

surface-contact, and rigid.

1.5KW high power asynchronous motor

Provide strong power, good performance, long life, high efficiency.



广泛用于工厂、维修店铺、学校、科创中心及科研单位教学演示使用,适合家用DIY, 航模零件、钟表零件加工; 可加工钛、不锈钢、45号钢、铁、铝、铜等各类有色金属和木材、尼龙等各类软材料。

Widely used in factories, maintenance shops, schools, science and technology innovation centers and scientific research units teaching demonstration use, suitable for household DIY, model airplane parts, clock parts processing;

Can process titanium, stainless steel, 45 steel, iron, aluminum, copper and other non-ferrous metals and wood, nylon and other soft materials.













펯 믁	Model	CTZD45
最大钻孔直径	Drilling Capacity	45mm
最大面铣能力	Face Milling Capacity	80mm
最大立铣能力	End Milling Capacity	32mm
最大攻丝能力	Threading capacity	M30
工作台尺寸	Table size	800x240mm
T型槽尺寸	T-slots size	14mm
工作台行程(X,Y行程)	Table travel (X-, Y-Axis)	580, 275mm
主轴箱头行程	Head travel (Z-Axis)	450mm
主轴锥度	Spindle taper	MT4
主轴行程	Spindle travel	130mm
主轴自动进给范围 (级数)	Quill Feed Rates (Grade)	0.06~0.30/prm (3)
主轴轴心到立柱导轨距离	Max. Spindle to Column	260mm
主轴箱左右倾斜	Head tilt	45°
主轴转速 (级数)	Spindle speeds (Grade)	80~1250rpm (6)
电机功率	Motor Power	1500W
净重	N.W.	400KG
外形尺寸	Overall dimensions	1150x1070x1430mm

产品外形尺寸为手工测量,存在较小误差,为正常情况,具体以实物为准。

The dimensions of the product are measured manually, and there is a small error, which is normal, and the actual product shall prevail.

WWW.AHCT.IX.COM